



PRODUCT DATA SHEET

SASOLWAX 5603

Revision: 15.03.2010

Property	Method	Unit	Specification	
Congealing point	ASTM D 938	°C	56,0	- 58,0
Oil content	ASTM D 721	%	0,00	- 0,50
Needle penetration 25°C	ASTM D 1321	1/10mm	15	- 19
Color Saybolt	ASTM D 156	-	29	- 30

This publication/data sheet and the information within were assembled and checked with utmost care and are to be regarded as accurate as of the date of issue. Nevertheless Sasol Wax GmbH takes no responsibility or warrant for its timeliness, completeness, quality or correctness. This publication/data sheet is for information only and does not warrant any particular product properties. It is the user's obligation to check the products and use them safely as well as to comply with all applicable laws and regulations. Sasol Wax GmbH shall not be responsible for any damage or injury in particular resulting from use, other than the stated use of the material, from any failure to abide to recommendations, or from any dangers inherent in the nature of the material. It is recommended to contact the manufacturer for further information, especially if it is intended to use the product for applications other than the stated. In addition, the most recent version of our General Business Conditions will apply.

Sasol Wax GmbH

Worthdamm 13-27, 20457 Hamburg, Postanschrift: Postfach 11 02 49, 20402 Hamburg
Telefon: +49 40 78115-0 Telefax: +49 40 78115-777 wax@de.sasol.com www.sasolwax.com

Geschäftsführung: Dr. Thomas Lüdemann
Vorsitzender des Aufsichtsrats: Francois Conradie
Registergericht Hamburg: HRB 73963 USt-IdNr./VAT No.: DE 118 922 039 Steuer-Nr./Tax-No. 27/164/00096

